

New Reliance XL

Plastic Lens Polish From PSI



Features & Benefits

- Quality, economical plastic lens polish
- Designed for use on processing lines with a mix of all lens materials
- Good polish for AR coating applications
- Utilizes newest anti-foam and non-freezing formulation
- Works well in single bowl and central slurry applications
- Maintains consistent Baume' reading
- Consistent stock removal on Plastic, Mid-Index, High-Index and Polycarbonate lens materials
- Surface quality rating of 7.5

Specifications

Package Size:	3317G - Gallon 3317P - 5-Gallon Pail
Baume:	20°
pH:	3.6
Particle Size (Coulter):	D50 - 2.1m
Surface Quality Rating:	7.5

Recommended Usage

Polish Cycle:	6 to 7 minutes
Pin Pressure:	16 to 18 pounds or .4 bars
Speed:	High
Temperature:	Maintain at 55° to 65° F

PSI Reliance Production Yields

Lens Type	Production Volume			Surface Quality		
	High	Medium	Low	Excellent	High	Average
CR39	X				X	
High Index		X			X	
Polycarbonate		X			X	



Practical Systems, Inc.

11617 Prospect Road • Odessa FL 33556
(800) 237-8154 • Fax (800) 330-3800
(727) 376-7900 • Fax (727) 372-1900



LOOK TO PSI

Performance • Service • Integrity